

Mojave Slate

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile	
Size*	12" x 12" / 305mm x 305mm	
Overall Thickness*	.080" / 2.0mm	
Wearlayer	4 mil / 0.10mm - PVC	
Construction	Layered plank consisting of wearlayer, film and backing.	
Edge	Square	
Standard Colors	12" x 12": 5 standard colors	
Installation Method	Glue Down	
Wear Limited Warranty	20-Year Residential / 10-Year Light Commercial	
Recycled Content	This product contains a minimum 50% recycled content. 100% recyclable post-use.	
Packaging	12" x 12": 36 ft ² (3.34 m ²) per carton 36 pieces per carton 72 cartons per pallet 18 pallets per 20' container	
Weight Per Carton	31lbs / 14.06kg	
Product Testing		
Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



***All measurements are nominal.**

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

